



BCO Mille-6 Rugged Charger for St@r Mille Battery





BCO Mille-6

Rugged Charger for St@r Mille Battery



- Up to six battery charge simultaneously
- Sealed and Fanless design
- Aluminum Housing designed to withstand Shock and Vibration
- Charge Led Indicator
- Waterproof IP66 (with battery)
- Wide range Input Voltage (15 — 36 Vdc)
- MIL-STD 810F
- MIL-STD 461E

Model BCO Mille-6

Mechanical and Environment


Dimension:	200x424x128 mm
Weight:	4 Kg (Without Battery)
Fixing holes:	4 x M6
Operation Temp.:	0°C to +40°C
IP Proof:	IP66
High Temperature:	MIL-STD-810G M.501
Low Temperature:	MIL-STD-810G M.502
Temperature Shock:	MIL-STD-810G M.503
Solar Radiation:	MIL-STD-810G M.505
Rain:	MIL-STD-810G M.506
Salt Fog:	MIL-STD-810G M.509
Sand and Dust:	MIL-STD-810G M.510
Vibration:	MIL-STD-810G M.514
Shock:	MIL-STD-810G M.516
Acid Atmosphere:	MIL-STD-810G M.518
Electromagnetic:	MIL-STD-461E

User Control

Control:	Power On Button
LED Indicator:	Power On
	Battery Charging / End Charge
	Error

Power Specification

Power Input:	15 — 36 Vdc (Nominal 24 Vdc)
	120 Watt (max)
Cable:	5 meters 2 x 16AWG



Stabilimento: 00071 Pomezia (Rm) - Via dei Castelli Romani, 24

Tel. 003969105503- Fax 003969105504

Mail lemsrl@lemsrl.it – P.E.C. lemsrl@arubapec.it